

MATERIAL SAFETY DATA SHEET

H	2
F	0
R	0
P	B

SECTION I - PRODUCT IDENTIFICATION

TRADE NAME: STRONGFAST
 CHEMICAL FAMILY/SYNONYMS: Portland Cement Mortar, lime, silica
 MANUFACTURER: W. R. BONSAL COMPANY, P.O. BOX 241148, CHARLOTTE, N. C. 28224
 EMERGENCY PHONE: (704) 525-1621 Mr. Fred Goeman

SECTION II - HAZARDOUS INGREDIENTS

DESCRIPTION	CAS #	PERCENT	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE (MM HG)
			TLV	PEL	
HYDRAULIC CEMENT	65997-15-1	12-16	10 mg/m ³		N/A
CRUSHED STONE (ROCK GRAVEL)	1317-65-3	30-45	10 mg/m ³		
SAND (FIELD SAND)*	7631-86-9	30-45	0.1 mg/m ³		
AMORPHOUS SILICA	60676-86-0	0-4	10 mg/m ³		

* % IS DETERMINED BY AIR BORNE SAMPLES

NOTE: Previous air monitoring during employee exposure to this product has indicated typical airborne respirable quartz fractions of up to 3%.

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	N/A	SPECIFIC GRAVITY (H ₂ O=1)	2.6 2.7
VAPOR PRESSURE (mmHg.)	N/A	% VOLATILE BY VOLUME (%)	0
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE	N/A
SOLUBILITY IN WATER:	Slight (0.1-1.0%)		

APPEARANCE & ODOR: Fine, gray powder mixed with sand and/or rock, no odor.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT: Will not ignite FLAMMABLE LIMITS N/A
 EXTINGUISHING MEDIA: None
 SPECIAL FIRE FIGHTING PROCEDURES: None
 UNUSUAL FIRE AND EXPLOSION HAZARD : None

Prepared By:

Friedrich Goeman
 Friedrich Goeman

MATERIAL SAFETY DATA SHEET

PRODUCT: STRONGFAST

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Respirable Dust - PEL = 0.1 mg/m³

EFFECTS OF OVEREXPOSURE: Excess exposure by inhalation over an extended period of time may result in the development of pulmonary diseases including pneumoconiosis and silicosis. Prolonged contact can produce skin irritation and dermatitis. Abrasive, skin and eye irritant.

EMERGENCY FIRST AID: **Inhalation:** remove from exposure. If not breathing, give artificial respiration, if breathing difficult, give oxygen, consult a physician. **Eye Contact:** flush thoroughly with water for 15 minutes. consult a physician. **Skin Contact:** wash thoroughly with soap and water.

SECTION VI - REACTIVITY DATA

STABILITY: UNSTABLE _____ STABLE X
CONDITIONS TO AVOID: N/A

INCOMPATIBILITY (MATERIALS TO AVOID): Highly alkaline. Strong acids may cause violent, exothermic reaction, evolve toxic gases/vapors, depending on type acid.

HAZARDOUS DECOMPOSITION PRODUCTS: N/A

HAZARDOUS POLYMERIZATION: MAY OCCUR _____ WILL NOT OCCUR X

CONDITIONS TO AVOID: N/A

SECTION VII - SPILL OR LEAK PROCEDURES

IN CASE MATERIAL IS RELEASED OR SPILLED: Use personal protective equipment to prevent dust exposures and protect against alkali burns or irritation. Sec. 8.
WASTE DISPOSAL METHOD: Dispose of in accordance with Federal, State and local regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (TYPE): NIOSH/MSHA approved for protection against silica and nuisance dusts.

VENTILATION:

Local Exhaust: Yes

Special: None

Mechanical: None

Other:

PROTECTIVE GLOVES: Rubber, PVC, Neoprene **EYE PROTECTION:** Goggles

OTHER PROTECTIVE EQUIPMENT: Rubber boots, arm sleeves and aprons when necessary to prevent skin contact.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS IN HANDLING AND STORING: Store in manner to prevent contact with strong acids. Avoid contact with water to preserve product.

OTHER PRECAUTIONS: None